

POLAR INDUSTRIES, Inc.

PO Box 293 Fisher Branch, MB R0C 0Z0 Tel: 204-372-8482 Fax: 204-372-8479

www.polarindustries.net

Sales Office: 3801 Howell Bend Ct. Oviedo, Fl. 32765 Tel. (407) 677-6664 Fax (407) 678-6684

POLAR PREMIUM - 7010 Series

GREEN CONCRETE COAT EPOXYTM - Non VOC

Applications:

DDODEDTIEG

7010 is a sprayable one (1) component non-VOC, water resistant, gloss HiOmega Natural Polyurethane epoxy coating cured by sunlight or UV light at 230 - 280

7010 concrete epoxy is designed for application on all concrete, marble, limestone, stone surfaces, indoor and outdoor.

7010 concrete epoxy provides water impermeable coating, heat resistant binding with the concrete. Can fill cracks providing strength and flexibility.

7010 is available in clear and white and can be tinted to a wide variety of custom colours.

PROPERTIES - 7010 Series				
Feature	Unit	Value	Measure Method	
Pour Point	°C	-10	Factory Prescription	
Kin. Viscosity by 23°C	mm ² /s	1344	DIN 53 019	
Density sp. Weight	g/cm ³	1069	DIN EN ISO 3675	
Working Temperature	45 - 120 °F surface temp	55-77		
Gel time by 23° C (1.5 kg accretion)	min	55	According application	
Curing Time	min	30 in sunlight	According application	
Set Time	min	4 under UV radiation		
Food Grade				

REMARKS FOR PROCESSING:

The optimal processing temperature is given by $12^{\circ}C \le T_p \le 30^{\circ}C$. All devices can be cleaned by acetone or a water/acetone mixture.

POLAR PREMIUM - 7010 Series GREEN CONCRETE COAT EPOXYTM - Non VOC

Agent	Findings	Agent	Findings
Solvents		Salts	
Gasoline	R	NaC1 3 %	R
(Bio) Diesel	R	NaC1 Saturated	R
Methanol	R	CaC1 ₂ Saturated	R
Acetone	swelling		
Acids		Lyes	
HC1	R	NaOH	slow saponification
H ₃ PO 4	R		1
НСООН	R		
CH ₃ COOH	R		
H_2SO_4	oxidation	КОН	slow saponification
HNO3	oxidation		-
R = Resistant			
DISPOSAL			
Remains can be chopped	l up and be composted or	burned.	
SAFETY PRECAUTIO	DNS		
	(including gloves and go	aglas)	